



**Ambient**   
TECHNOLOGIES®

Remote Control Technology Designed for Total Comfort

# Ambient

## TECHNOLOGIES®

**Ambient Technologies, offers a broad line of remote controls and accessories designed for total comfort.**

Ergonomic design, ease of operation and soft-touch finish combine to enhance the comfort, luxury and convenience of any gas fireplace.

**To ensure product reliability, each remote features a radio frequency operating system.**

Radio frequency allows for multiple security codes – which virtually eliminates interference from other home appliances such as televisions, DVD's and stereos – and each remote will operate at a maximum distance of 30 feet with no interference from objects between the user and the receiver.

**Innovative technology, advanced engineering and a 20-step quality control program produce the finest remote controls available in the industry.**

Our remotes and accessories have been engineered for compatibility with ALL brands of gas fireplaces, logs, inserts and stoves in today's market, and are fully warranted for 5 years.

**Our pledge for comfort extends beyond the showroom.**

Top-notch technical support is automatically included as part of the package. Our toll-free number is staffed by knowledgeable technicians, ready to assist before, during and after installation so that customers can be totally comfortable when choosing **Ambient Technologies.**

## DC Table Top/Wall Mount Remote Controls for Millivolt or 24V Systems

### TLT

- Thermostat "Touch" ON/OFF remote control
- LCD display with backlighting, temperature, "flame on" indicator, on/off sound indicator and "battery low" indicator
- Childproof protection
- Thermal-safety shutdown (transmitter)
- Wall mount bracket
- 16 security codes
- Battery receiver



### TLM

- Manual "Touch" ON/OFF remote control
- LCD display with backlighting, temperature, "flame on" indicator, on/off sound indicator and "battery low" indicator
- Childproof protection
- Thermal-safety shutdown (transmitter)
- Wall mount bracket
- 16 security codes
- Battery receiver



 touch • light®  
Touch Sensitive Fireplace Remote



## AC Remote Controls for Millivolt or 24V Systems

### **TOTAL SYSTEM CONTROL**



#### **RCSITE (For SIT 820 valves, Natural or LP Gas)**

- Standard thermostat ON/OFF remote control
- 3-step flame height adjustment for SIT valve
- 3-speed blower control with adjustable automatic ON/OFF delay
- LCD display with backlighting, temperature, "flame on" indicator and "battery low" indicator
- Childproof protection
- Soft-touch finish
- Thermal-safety shutdown (transmitter)
- 16 security codes
- 110V receiver
- 6 hr. optional safety shutdown (receiver)



#### **RCSTEB**

- Standard thermostat ON/OFF remote control
- 3-speed blower control with adjustable automatic ON/OFF delay
- LCD display with backlighting, temperature, "flame on" indicator and "battery low" indicator
- Childproof protection
- Soft-touch finish
- Thermal-safety shutdown (transmitter)
- 16 security codes
- 110V receiver
- 6 hr. optional safety shutdown (receiver)



#### **RCSTE**

- Standard thermostat ON/OFF remote control
- LCD display with backlighting, temperature, "flame on" indicator and "battery low" indicator
- Childproof protection
- Thermal-safety shutdown (transmitter)
- 16 security codes
- 110V receiver
- 6 hr. optional safety shutdown (receiver)



#### **RCBE**

- ON/OFF remote control
- Signal indicator
- "Battery low" indicator
- 16 security codes
- 110V receiver
- 6 hr. optional safety shutdown (receiver)

## DC Remote Controls for Millivolt or 24V Systems

### RCT

- 7-day (5/2) programmable thermostat ON/OFF remote control
- LCD display with backlighting, temperature, time, "flame on" indicator and "battery low" indicator
- Countdown timer (120 min.)
- Childproof protection
- Soft-touch finish
- Thermal-safety shutdown (transmitter)
- Wall mount bracket
- 16 security codes
- Battery receiver with easy battery access
- 6 hr. optional safety shutdown (receiver)



### RCST

- Standard thermostat ON/OFF remote control
- LCD display with backlighting, temperature, "flame on" indicator and "battery low" indicator
- Childproof protection
- Thermal-safety shutdown (transmitter)
- 16 security codes
- Battery receiver with easy battery access
- 6 hr. optional safety shutdown (receiver)



### RCMT

- Deluxe ON/OFF remote control
- 90 min. countdown timer
- LCD display with backlighting, temperature, time, "flame on" indicator and "battery low" indicator
- Childproof protection
- Soft-touch finish
- Thermal-safety shutdown (transmitter)
- 16 security codes
- Battery receiver with easy battery access
- 6 hr. optional safety shutdown (receiver)



### RCB

- ON/OFF remote control
- Signal indicator
- "Battery low" indicator
- 16 security codes
- Battery receiver with easy battery access
- 6 hr. optional safety shutdown (receiver)



**EASY BATTERY ACCESS PLATE FOR WALL MOUNTING**

Available in black or white

## DC Remote Controls for Maxitrol® & Concentric Varitap/ Latchtap Flame Height Control Valve Systems

### RCSTHC (Maxitrol System)

- Standard thermostat ON/OFF remote control with flame height control
- LCD display with backlighting, temperature, "flame on" indicator and "battery low" indicator
- Childproof protection
- Thermal-safety shutdown (transmitter)
- 16 security codes
- Battery receiver with easy battery access
- Six hour optional safety shutdown (receiver)



### RCBHC (Maxitrol, Concentric Varitap/Latchtap Systems and Ameriflame AF1000)

- ON/OFF remote control with flame height control
- Signal indicator
- 16 security codes
- Battery low indicator
- Battery receiver with easy battery access
- 6 hr. optional safety shutdown (receiver)



Maxitrol® is a registered trademark of Mertik Maxitrol.

## Wall Mounted Remotes for Millivolt or 24V Systems



### WWTD (DC Receiver)

- 7-day (5/2) programmable ON/OFF wall thermostat
- LCD display with backlighting, temperature, time, "flame on" indicator and "battery low" indicator
- Countdown timer
- Childproof protection
- Thermal-safety shutdown (transmitter)
- 16 security codes
- Battery receiver with easy battery access
- 6 hr. optional safety shutdown (receiver)



## Wall Switch or Timer Remote for Millivolt or 24V Systems



### WMTD

- ON/OFF wall switch/timer remote control
- Back lit LCD display with, temperature, time, "flame on" indicator and "battery low" indicator
- Flush Mount (no electric box needed)
- Countdown timer (set-up for resort and rental applications) 30/60/90 or 60/120/180
- Childproof protection
- Thermal-safety shutdown (transmitter)
- 16 security codes
- Battery Receiver

## Wired Controls for Millivolt or 24V Systems

### WT

- Wall Mounted Digital Thermostat with 25' of wire and spade connectors
- LCD display with backlighting, temperature, time, "flame on" indicator and "battery low" indicator
- Flush Mount
- Temperature setting range from 40° to 99° F



### MVWS

- Wall Switch with 15' of wire
- Mounts in wall box



### ELSK

- Refractory log with On/Off switch and 12" of wire



## Vented Log Valve Kits



### MMVK – Manual Valve Kit

- Valve
- Handle and handle extension



### SPK-NG and SPK-LP Safety Pilot Kit

- Available in natural or LP gas
- For use with vented logs
- Pilot assembly and screws
- Handle extension
- 3/8" pipe fittings
- Heat shield
- Vermiculite (with LP kits)



### MVVK – Millivolt Valve Kit

- Available in natural or LP gas
- For use with vented logs
- Millivolt valve
- Pilot assembly and screws
- ON/OFF switch
- Flex connectors
- Heat shield
- Vermiculite (with LP kits)



### Concentric Varitap Hi/Lo Valve Kit

- Available in natural or LP Gas
- For use with vented logs
- Pilot assembly and screws
- Handle extension
- 3/8" pipe fittings
- Heat shield
- Vermiculite (with LP kits)

## Receiver Covers



Fiber ceramic log remote receiver cover-RRCL



Fiber ceramic ember remote receiver cover-RRCE



Metal remote receiver cover-RRCM

## Decorative Valve Covers



Fiber ceramic millivolt valve cover-VWFMVC



Fiber ceramic pilot safety or manual valve cover-VWFMC

## Additional Accessories

- Flex connectors – Dormont stainless steel 3/8" NPT male connector "x" combo 3/8" NPT female and 1/2" NPT male connector
- Available in 12", 18", 24", 30" and 36" sizes
- 36" wire kits - Available for all remotes
- 25' wire kit - Available for millivolt remotes

Appropriate industry logos to show? Old brochure had none.

# Ambient

TECHNOLOGIES®

149 Cleveland Drive • Paris, KY 40361  
800-867-0454 • [www.ambienttechnologies.com](http://www.ambienttechnologies.com)  
© 2008 Ambient Technologies

Your Ambient Dealer: